

Application Instructions for Flamecheck™

FIF Clear Coat-IN
FIF Clear Coat-X



Flamecheck™
Simply Safer.

DIRECTIONS FOR USE: Flamecheck™ FIF Clear Coat-IN and FIF Clear Coat-X are flame retardants for paintable surfaces, such as wood, paneling, plastic flowers, decorations and other building materials. Flamecheck™ FIF Clear Coat is non-toxic and environmentally friendly, with Low VOC's. This is a water based latex acrylic poly finish.

Coverage: One gallon of Flamecheck™ FIF Clear Coat will flameproof an average 200 sq. ft. (2 coats / 2 mils thick required for "Class A" finish). Mix well. Do not dilute.

Tools: Smaller applications may use a high-quality paint brush or roller. Larger applications use an airless paint sprayer that operates out of a 5-gallon container. Dipping the item into the FIF Clear Coat is an acceptable application used for items like plastic flowers and decorations.

Surface Preparations: Be sure the material you are treating is clean and free of dust, grease and unsightly spots. Repair all surface imperfections and sand to remove blemishes, using a finer sandpaper to remove scratches until smooth. After sanding remove dust using a tack rag or soap and water.

Clean Up: Clean all equipment using soap and water immediately after use. Clean up spills using soap and water. Dispose of contaminated rags as local and state regulations require.

Dry Time: This product dries in 2-4 hours at 77° with no more than 50% humidity. Humidity and low temperatures will extend dry times. Recoat in 48 hours. After final coating on horizontal surfaces allow 48 hours for light use and 72 hours for heavy use. Do not get wet until fully cured (4 days).

SAFETY NOTE: Use standard paint precautions, such as providing adequate ventilation. Keep away from the face and eyes and store Flamecheck™ FIF Clear Coat out of reach of children. Wear safety gear: goggles, mask, overalls and gloves. Cover electrical equipment, heating and cooling vents and use drop cloths to protect from drips or spills.

Certification: May require application by a Certified General Applicator to comply with requirements in CA, NY and MA.

Disposal: Follow all state and local guidelines for water-based paint disposal even after the container is empty.

Disclaimer: Flamecheck makes no guarantee, nor any express or implied warranty of merchantability or fitness for a particular use regarding the suitability of this product for any particular purpose or use, nor does it assume any liability arising out of the application or mis-use of this product. Application techniques vary; therefore, it is the end user's responsibility to test and verify the application techniques and suitability of this product for the intended use. Always test after application. Flamecheck International LLC only warrants the quality control of this product. For the complete disclaimer regarding this product, visit www.flamecheck.com

Keep out of the reach of children. Ingestion of this product, or contact with eyes or skin, can result in serious injury. Use in a well-ventilated area. If swallowed CONTACT A MEDICAL PROFESSIONAL IMMEDIATELY. Contact with eyes or skin, flush with copious amounts of water for 15 minutes. If irritation persists, seek medical attention. **Never give anything by mouth to an unconscious person.**

REFER TO OUR WEBSITE AT www.flamecheck.com FOR ADDITIONAL IMPORTANT INFORMATION.

CERTIFICATES

Flamecheck™ FIF Clear Coat meets or exceeds a "Class A" finish when properly applied for these test standards:

- ✓ ASTM E-84
- ✓ UL 723
- ✓ UBC 8-1(42-1)
- ✓ NFPA 255

